

# Epifanes Fiberglass Prep Cleaner

Degreaser for fiberglass, bare steel, alloy and epoxy resin. Perfectly removes all wax, fiberglass agents oil, grease, tar or any other contamination of gel coat.

For the removal of fiberglass objects formed by mall, the inside of the mall is coated with a waxy substance. Parts of this waxy substance are left on the gel coat and can remain for years on the gel coat. Before a paint system can be applied and in order to secure bonding with the gel coat this waxy substance must be fully removed. If the gel coat is not (fully) degreased, adhesion on the gel coat is minimal and any paint system will fail. Degreasing must be executed before sanding in order to avoid sanding the way substance into the sand marks. Epifanes Fiberglass Prep Cleaner is not suited for degreasing one-component paint or varnish systems.

Type	Mixture of acetate and hydrocarbon
Color	colorless
Density	0.97 kg/dm <sup>3</sup>
Flashpoint	24°C
Characteristics	High degreasing power.
Handling	Wipe surface with a non fluffy clean cloth soaked with Epifanes Fiberglass Prep Cleaner. Continue by wiping the surface with a clean dry cloth. Change cloths regularly in order to avoid just replacement of contamination instead of actual removal. When the gel coat is sanded, repeat degreasing once more.
Safety/	This product is flammable and harmful when inhaled. Avoid breathing vapor. Skin and eye irritant. Avoid contact with eyes and prolonged and repeated contact with skin. In case of eye contact, flush thoroughly with tap water for at least 15 minutes and get immediate medical attention. Keep away from heat and open flame. Use only with adequate ventilation. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Store in a cool well ventilated area. Do not empty into drains. Close container after each use.
Personal protection	
- eyes	Use suitable protective glasses
- skin	Use protective clothing and gloves
- breathing	Use appropriate breathing apparatus