

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 06.11.2002

1 Identification of the substance/preparation and of the company/ undertaking

- Product details
- Trade name: Epifanes Interimcoat component B (cure)
- Application of the substance / the preparation
Coating material
Curing agent of a two-component primer and/or intercoat
- Manufacturer/Supplier:
W.HEEREN & ZOON BV
Postbus 166
1430 AD Aalsmeer
tel. +31-297-360366
fax. +31-297-342078
- Further information obtainable from: Department Research & Development
- Information in case of emergency: See under Manufacturer/Supplier

2 Composition/information on ingredients

- Chemical characterization
- Description:
Resin mixture
Solvent mixture with pigment additives
Mixture of reactive synthetic binder and organic solvents

- Dangerous components:

CAS: 108-88-3 EINECS: 203-625-9	toluene Xn, F; R 11-20	40.0%
	Polyaminoamide Xi; R 41	39.996%
CAS: 1330-20-7 EINECS: 215-535-7	xylene Xn; R 10-20/21-38	10.0%
CAS: 78-93-3 EINECS: 201-159-0	butanone Xi, F; R 11-36-66-67	5.56%
CAS: 90-72-2 EINECS: 202-013-9	2,4,6-tris(dimethylaminomethyl)phenol Xn; R 22-36/38	2.222%

- Additional information:
For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description:



Xn Harmful
F Highly flammable

- Information concerning particular hazards for human and environment:
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 11 Highly flammable.
R 20 Harmful by inhalation.
R 41 Risk of serious damage to eyes.

(Contd. on page 2)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 06.11.2002

Trade name: Epifanes Interimcoat component B (cure)

(Contd. of page 1)

- Classification system:
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- General information:
Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call for a doctor immediately.

5 Fire-fighting measures

- Suitable extinguishing agents:
CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents:
Water
Water with full jet
- Protective equipment: Wear fully protective suit.

6 Accidental release measures

- Person-related safety precautions:
Ensure adequate ventilation
Wear protective clothing.
- Measures for environmental protection:
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- Handling:
- Information for safe handling: Work only in fume cupboard.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
Protect from heat and direct sunlight.

(Contd. on page^{GB}3)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 06.11.2002

Trade name: Epifanes Interimcoat component B (cure)

(Contd. of page 2)

8 Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.

- Ingredients with limit values that require monitoring at the

Workplace	
OES	Short-term value: 574 mg/m ³ , 150 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
1330-20-7 xylene	
OES	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk
78-93-3 butanone	
OES	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm IOELV, Sk,

- Additional information:
The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Avoid contact with the eyes and skin.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- Respiratory protection:
Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Safety glasses

9 Physical and chemical properties

- General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

- Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

(Contd. on page 4)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 06.11.2002

Trade name: Epifanes Interimcoat component B (cure)

(Contd. of page 3)

• Flash point:	< 21°C
• Ignition temperature:	500°C
• Self-igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
• Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
• Vapour pressure at 20°C:	29 hPa
• Density at 20°C:	0.91 g/cm ³
• Solubility in / Miscibility with water:	Insoluble.
• Viscosity:	
Kinematic at 20°C:	30 s (ISO 4 mm)
• Solvent content:	
Organic solvents:	60.0 %
• Solids content:	40.0 % (VB% 1h150 C)

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.
- Dangerous decomposition products:
No dangerous decomposition products known.

11 Toxicological information

- Acute toxicity:

- LD/LC50 values relevant for classification:

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

(Contd. on page 5)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 06.11.2002

Trade name: Epifanes Interimcoat component B (cure)

(Contd. of page 4)

12 Ecological information

- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- Product:
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation:
Disposal must be made according to official regulations.

14 Transport information

- Land transport ADR/RID (cross-border)



- ADR/RID class: 3 F1 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: II
- Hazard label 3
- Description of goods: 1263 PAINT RELATED MATERIAL

- Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label 3
- Packaging group: II
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: PAINT RELATED MATERIAL

- Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label 3
- Packaging group: II

(Contd. on page 6)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 06.11.2002

Trade name: Epifanes Interimcoat component B (cure)

(Contd. of page 5)

- Proper shipping name: PAINT RELATED MATERIAL

15 Regulatory information

- Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- Code letter and hazard designation of product:
Xn Harmful
F Highly flammable
- Hazard-determining components of labelling:
toluene
- Risk phrases:
11 Highly flammable.
20 Harmful by inhalation.
41 Risk of serious damage to eyes.
- Safety phrases:
2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
36/39 Wear suitable protective clothing and eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
- National regulations:
- Technical instructions (air):

Class	Share in %
II	50.0
III	7.8
- Waterhazard class:
Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant R-phrases
10 Flammable.
11 Highly flammable.
20 Harmful by inhalation.
20/21 Harmful by inhalation and in contact with skin.
22 Harmful if swallowed.
36 Irritating to eyes.
36/38 Irritating to eyes and skin.
38 Irritating to skin.
41 Risk of serious damage to eyes.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.
- Department issuing MSDS: Department Research & Development
- Contact: T.J.H.M. van Steenes